

KK-ABSORB15**Odor Absorber Masterbatch****Product information**

KK-ABSORB15 is an additive masterbatch that produced in order to eliminate the bad smell of the goods produced from recycled raw materials without using any odor.

Typical Applications:

Rubber Compound, Recycled PE or PP.

Recommendation of addition rate: 0,5-1,5%

Product Data:

Property	Test Method	Unit	Value
Physical Properties			
Based Resin	-	-	Polyolefin
Melt Flow Rate (190°C-2,16 kg)	ASTM D 1238	g/10 dk	5-12
Density (23°C)	ASTM D 792	g/cm ³	1,55±0,03
Moisture	Internal Method	%	≤0,2
Color	-	-	White

Packaging:

It is packaged as 25 kg in aluminum boxes.

Storage&Handling:

KK-ABSORB15 should be stored in a manner that avoids direct exposure to sunlight and heat (T<30°C). This compound should be used within 6 months after its production date. After this time it's necessary to dry the material before extrusion.

KABKOM KİMYA SANAYİ VE TİCARET A.Ş.

İbni Melek OSB TOSBİ Yol 1 No:13 PK:35900 Tire/İZMİR

Tel: +90 (216) 807 20 04 (pbx)

www.kabkom.com.tr

info@kabkom.com.tr

satis@kabkom.com.tr

