

**KK-AOX6810**

Synergistic Antioxidant Masterbatch

**Product Applications:**

KK-AOX6810 is phenolic primary antioxidant and phosphite secondary antioxidant thermal stabilizer. KK-AOX6810 can be used for a processing and long-term thermal stabilizer system.

KK-AOX6810 is a Multifunctional Additive for HFFR cables compounds, cables production and other filled compounds.

**Recommendation of addition rate:** 3-5%

**Product Data**

Property	Unit	Value
<b>Physical Properties</b>		
Carrier Resin	-	Polyolefin
MFI (190°C-2,16 kg)	g/10 min	40±10
Density	g/cm <sup>3</sup>	1,22±0,02
Total Additive Content	%	20

**Packaging:**

It is packaged as 15 kg in aluminum bags, 1000 kg pallets.

**Storage&Handling:**

KK-AOX6810 should be stored in a manner that avoids direct exposure to sunlight and heat (T<30°C). This compound should be used within 6 months after its production date. After this time it's necessary to dry the material before extrusion.

**KABKOM KİMYA SANAYİ VE TİCARET A.Ş.**

İbni Melek OSB TOSBİ Yol 1 No:13 PK:35900 Tire/İZMİR

Tel: +90 (216) 807 20 04 (pbx)

[www.kabkom.com.tr](http://www.kabkom.com.tr)[info@kabkom.com.tr](mailto:info@kabkom.com.tr)[satis@kabkom.com.tr](mailto:satis@kabkom.com.tr)